

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.11.2018

Version number 4

Revision: 30.11.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Akepox 1099 Komponente B**

Article number: 11753/11754, 11755, 13752

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Reaction resin
Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.11.2018

Version number 4

Revision: 30.11.2018

Trade name: Akepox 1099 Komponente B

(Contd. of page 1)

· Hazard pictograms

GHS05 GHS07 GHS08

· Signal word

Danger

· Hazard-determining components of labelling:

2-piperazin-1-ylethylamine
 1,3-Cyclohexanedimethanamine
 m-phenylenebis(methylamine)
 phenole, styrenated

· Hazard statements

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H361 Suspected of damaging fertility or the unborn child.
 H372 Causes damage to organs through prolonged or repeated exposure.

· Precautionary statements

H412 Harmful to aquatic life with long lasting effects.
 P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read label before use.
 P260 Do not breathe vapours.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**· Results of PBT and vPvB assessment

· PBT: Not applicable.
 · vPvB: Not applicable.

*

SECTION 3: Composition/information on ingredients· **3.2 Chemical characterisation: Mixtures**

· Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.11.2018

Version number 4

Revision: 30.11.2018

Trade name: Akepox 1099 Komponente B

(Contd. of page 2)

· <u>Dangerous components:</u>		
CAS: 140-31-8 EINECS: 205-411-0 Index number: 612-105-00-4 Reg.nr.: 01-2119471486-30-0000	2-piperazin-1-ylethylamine ⚠ Acute Tox. 3, H311 ⚠ Repr. 2, H361; STOT RE 1, H372 ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317 Aquatic Chronic 3, H412	25-50%
CAS: 2579-20-6 EINECS: 219-941-5 Reg.nr.: 01-2119543741-41-xxxx	1,3-Cyclohexanedimethanamine ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312 Aquatic Chronic 3, H412	25-50%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50-xxxx	m-phenylenebis(methylamine) ⚠ Skin Corr. 1B, H314 ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317 Aquatic Chronic 3, H412	12.5-25%
CAS: 69-72-7 EINECS: 200-712-3 Reg.nr.: 01-2119486984-17	Salicylic acid ⚠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302	1-5%
CAS: 61788-44-1 EINECS: 262-975-0 Reg.nr.: 01-2119980970-27	phenole, styrenated ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	1-5%
· <u>Additional information:</u> For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Take affected persons out into the fresh air.
Position and transport stably in side position.
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: If skin irritation continues, consult a doctor.
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Call for a doctor immediately.
Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions
Headache
Dizziness
Dizziness
Breathing difficulty
Profuse sweating
Nausea

- Information for doctor: The sensitizing effect of epoxide based resins is mainly caused by the concentration of epoxy resin polymers with a specific molecular weight ≤ 300 . The observed allergic dermal and respiratory appearances should be treated symptomatically in dependence of the severity. An epoxy resin based allergic disease belongs to a cell mediated (interaction of lymphocytes) type IV allergy.

(Contd. on page 4)

Revision: 30.11.2018

(Contd. of page 3)

- GE

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.11.2018

Version number 4

Revision: 30.11.2018

Trade name: Akepox 1099 Komponente B

(Contd. of page 4)

Store in cool, dry place in tightly closed receptacles.
Use only in well ventilated areas.
Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

No special measures required.

· **7.2 Conditions for safe storage, including any incompatibilities**

· Storage:

· Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.
Prevent any seepage into the ground.

· Information about storage in one common storage facility:

Store away from foodstuffs.

· Further information about storage conditions:

Store receptacle in a well ventilated area.
Keep container tightly sealed.

· Storage class:

8

· **7.3 Specific end use(s)**

No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities:

No further data; see item 7.

· **8.1 Control parameters**

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

140-31-8 2-piperazin-1-ylethylamine

Dermal	DNEL (Kurzzeit-akut)	20 mg/kg bw/day (ARB)
Inhalative	DNEL (Kurzzeit-akut)	21.4 mg/m ³ Air (ARB)
	DNEL (Langzeit-wiederholt)	10.6 mg/m ³ Air (ARB)

1477-55-0 m-phenylenebis(methylamine)

Dermal	DNEL (Langzeit-wiederholt)	0.33 mg/kg bw/day (ARB)
Inhalative	DNEL (Langzeit-wiederholt)	1.2 mg/m ³ Air (ARB)

69-72-7 Salicylic acid

Oral	DNEL (Kurzzeit-akut)	4 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	1 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	2 mg/kg bw/day (ARB)
		1 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	16 mg/m ³ Air (ARB)
		0.2-4 mg/m ³ Air (BEV)

· PNECs

140-31-8 2-piperazin-1-ylethylamine

PNEC (wässrig)	0.0058 mg/l (MW)
	0.058 mg/l (SW)

1477-55-0 m-phenylenebis(methylamine)

PNEC (wässrig)	0.0094 mg/l (MW)
	0.094 mg/l (SW)

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.11.2018

Version number 4

Revision: 30.11.2018

Trade name: Akepox 1099 Komponente B

(Contd. of page 5)

69-72-7 Salicylic acid

PNEC (wässrig)	162 mg/l (KA)
	0.02 mg/l (MW)
	0.2 mg/l (SW)
PNEC (fest)	0.166 mg/kg Trockengew (BO)
	0.142 mg/kg Trockengew (MWS)
	1.42 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· Personal protective equipment:
 · General protective and hygienic measures:

Use skin protection cream for skin protection.
 Clean skin thoroughly immediately after handling the product.
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the eyes and skin.

· Respiratory protection:

Short term filter device:
 Filter A/P2

· Protection of hands:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
 Preventive skin protection by use of skin-protecting agents is recommended.
 After use of gloves apply skin-cleaning agents and skin cosmetics.
 Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:
 STOKO EMULSION (<http://www.stoko.com>)
 Skin protection recommendation for skin cleaning after product handling:
 Kresto Classic (<http://debstoko.com>)
 Skin protection agent recommendation for skin aftercare:
 STOKO VITAN (<http://www.stoko.com>)
 The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.
 This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR
 Nitrile rubber, NBR

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.11.2018

Version number 4

Revision: 30.11.2018

Trade name: Akepox 1099 Komponente B

(Contd. of page 6)

- Chloroprene rubber, CR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material Value for the permeation: Level ≤ 6 , 480 min
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
 - For the permanent contact gloves made of the following materials are suitable:
 - Butyl rubber, BR
 - Butoject (KCL, Art_No. 897, 898)
 - Nitrile rubber, NBR
 - Camatril (KCL, Art_No. 730, 731, 732, 733)
 - Dermatril (Art_No. 740, 741, 742)
 - Chloroprene rubber, CR
 - Camapren (KCL, Art_No. 720, 722, 726)
 - As protection from splashes gloves made of the following materials are suitable:
 - Nitrile rubber, NBR
 - Dermatril (KCL, Art_No. 740, 741, 742)
 - Camatril (KCL, 730, 731, 732, 733)
 - Chloroprene rubber, CR
 - Camapren (KCL, Art_No. 720, 722, 726)
 - Not suitable are gloves made of the following materials:
 - Leather gloves
 - Strong material gloves
 - Eye protection:



Tightly sealed goggles
 - Body protection: Protective work clothing

* SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

- | | |
|---------|------------|
| Form: | Fluid |
| Colour: | Yellowish |
| Odour: | Amine-like |

- | | |
|-------------|----------------|
| · pH-value: | Not applicable |
|-------------|----------------|

· Change in condition

- | | |
|--|---------------|
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling range: | > 200 °C |

- | | |
|----------------|----------|
| · Flash point: | > 100 °C |
|----------------|----------|

- | | |
|-------------------------|--------|
| · Ignition temperature: | 315 °C |
|-------------------------|--------|

- | | |
|------------------------------|------------------------------|
| · Auto-ignition temperature: | Product is not selfigniting. |
|------------------------------|------------------------------|

- | | |
|-------------------------|---|
| · Explosive properties: | Product does not present an explosion hazard. |
|-------------------------|---|

· Explosion limits:

- | | |
|--------|------------|
| Lower: | 2.1 Vol % |
| Upper: | 10.5 Vol % |

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.11.2018

Version number 4

Revision: 30.11.2018

Trade name: Akepox 1099 Komponente B

(Contd. of page 7)

· Vapour pressure at 20 °C:	0.1 hPa
· Density at 20 °C:	1.03 g/cm ³
· Solubility in / Miscibility with water:	Fully miscible.
· Viscosity:	
Dynamic at 20 °C:	120 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** Strong exothermic reaction with acids.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Corrosive gases/vapours

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Harmful if swallowed, in contact with skin or if inhaled.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	972-1,055 mg/kg (r)
Dermal	LD50	1,510 mg/kg
Inhalative	LC50/4 h	13.3 mg/l (r)

140-31-8 2-piperazin-1-ylethylamine

Oral	LD50	2,097 mg/kg (rabbit) 1,470-2,140 mg/kg (rat)
Dermal	LD50	866 mg/kg (rabbit) 866-1,260 mg/kg (rat)

2579-20-6 1,3-Cyclohexanedimethanamine

Oral	LD50	700 mg/kg (rat)
Dermal	LD50	1,700 mg/kg (rabbit)

1477-55-0 m-phenylenebis(methylamine)

Oral	LD50	930 mg/kg (rat)
	NOEL	150 mg/kg (rat)
Dermal	LD50	3,100 mg/kg (rabbit)
Inhalative	LC50/4 h	2.4 mg/l (rat)
	LC50/1h	3.89 mg/l (rat)

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.11.2018

Version number 4

Revision: 30.11.2018

Trade name: Akepox 1099 Komponente B

(Contd. of page 8)

69-72-7 Salicylic acid

Oral	LD50	891 mg/kg (rat)
	NOAEL-Werte	250 mg/kg (rat) (OECD 416)
Dermal	LD50	>2,000 mg/kg (rabbit)
	LC50/48h	90 mg/l (Leuciscus idus)

61788-44-1 phenole, styrenated

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>5,010 mg/kg (rabbit)
		>2,000 mg/kg (rat)

- Primary irritant effect:
- Skin corrosion/irritation Causes severe skin burns and eye damage.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Suspected of damaging fertility or the unborn child.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Causes damage to organs through prolonged or repeated exposure.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**· 12.1 Toxicity****· Aquatic toxicity:****140-31-8 2-piperazin-1-ylethylamine**

EC50	511 mg/l (bacteria)
EC50/48h	58 mg/l (daphnia magna)
	494 mg/l (Selenastrum capricornutum)
EC20/0.5h	>1,000 mg/l (BES)
EC50/72h	>1,000 mg/l (pseudomonas putida)
	494 mg/l (Selenastrum capricornutum)
LC50/96h	2,190 mg/l (piscis)
	368 mg/l (Leuciscus idus)
	>100 mg/l (Oncorhynchus mykiss)
	>1,800 mg/l (poecilia reticulata)

2579-20-6 1,3-Cyclohexanedimethanamine

EC50	>1,000 mg/l (BES)
	90 mg/l (pseudomonas putida)
EC50/48h	64.7 mg/l (daphnia magna)
EC50/72h	58.4 mg/l (selenastrum capricornutum)
LC50/96h	130 mg/l (Leuciscus idus)

1477-55-0 m-phenylenebis(methylamine)

EC50/48h	15.2 mg/l (daphnia magna)
EC50/72h	12 mg/l (Scenedesmus subspicatus)
	20.3 mg/l (selenastrum capricornutum)
LC50/96h	>100 mg/l (Oncorhynchus mykiss)
	87.6 mg/l (Oryzias latipes)

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.11.2018

Version number 4

Revision: 30.11.2018

Trade name: Akepox 1099 Komponente B

(Contd. of page 9)

	>100 mg/l (Zebrabärbling)
69-72-7 Salicylic acid	
EC50	>3,200 mg/l (BES) (OECD 209)
LC50/24h	105-230 mg/l (daphnia magna)
EC50/48h	870 mg/l (daphnia magna) (OECD 202)
EC50/16h	380 mg/l (bacteria)
NOEC/21d	10 mg/l (daphnia magna) (OECD 202 II)
EC50/72h	>100 mg/l (green alge) (OECD 201)
LC50/96h	1,370 mg/l (piscis) (OECD 203)
	1,380 mg/l (pimephales promelas)
61788-44-1 phenole, styrenated	
EL50/48h	1-10 mg/l (daphnia magna)
EL50/72h	3.14 mg/l (Scenedesmus subspicatus)
LL50/96h	14.8 mg/l (piscis)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:**

Toxic for fish

· **Additional ecological information:**

· **General notes:**

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even small quantities leak into the ground.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Other adverse effects**

No further relevant information available.

* **SECTION 13: Disposal considerations**

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)
20 01 27*	paint, inks, adhesives and resins containing hazardous substances
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 10*	packaging containing residues of or contaminated by hazardous substances

· **Uncleaned packaging:**

· **Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· **Recommended cleansing agents:**

Alcohol

(Contd. on page 11)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.11.2018

Version number 4

Revision: 30.11.2018

Trade name: Akepox 1099 Komponente B

(Contd. of page 10)

acetone
Water, if necessary together with cleansing agents.

* SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA UN2735

· 14.2 UN proper shipping name

· ADR 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Cyclohexanedimethanamine, m-phenylenebis(methylamine))
· IMDG, IATA AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Cyclohexanedimethanamine, m-phenylenebis(methylamine))

· 14.3 Transport hazard class(es)

· ADR



· Class 8 (C7) Corrosive substances.
· Label 8

· IMDG, IATA



· Class 8 Corrosive substances.
· Label 8

· 14.4 Packing group

· ADR, IMDG, IATA II

· 14.5 Environmental hazards:

· Marine pollutant: Yes

· 14.6 Special precautions for user

Warning: Corrosive substances.
· Danger code (Kemler): 8
· EMS Number: F-A,S-B
· Segregation groups Alkalis
· Stowage Category A
· Segregation Code SG35 Stow "separated from" acids.

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· Transport/Additional information:

· ADR
· Limited quantities (LQ) 1
· Excepted quantities (EQ) Code: E
· Transport category 2
· Tunnel restriction code E

· IMDG

· Limited quantities (LQ) 1

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.11.2018

Version number 4

Revision: 30.11.2018

Trade name: Akepox 1099 Komponente B

(Contd. of page 11)

· Excepted quantities (EQ)	Code: E
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-CYCLOHEXANEDIMETHANAMINE, M-PHENYLENEBIS(METHYLAMINE)), 8, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances -
ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006
ANNEX XVII Conditions of restriction: 3
- National regulations:
- Information about limitation of use: Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.
- Waterhazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.
- VOC EU 0.0 g/l
- 15.2 Chemical safety
assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
 - H302 Harmful if swallowed.
 - H311 Toxic in contact with skin.
 - H312 Harmful in contact with skin.
 - H314 Causes severe skin burns and eye damage.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H318 Causes serious eye damage.
 - H332 Harmful if inhaled.
 - H361 Suspected of damaging fertility or the unborn child.
 - H372 Causes damage to organs through prolonged or repeated exposure.
 - H411 Toxic to aquatic life with long lasting effects.
 - H412 Harmful to aquatic life with long lasting effects.
- Recommended restriction of use refer to Technical Data Sheet (TDS)
- Department issuing SDS: Laboratory
- Contact: Dieter Zimmermann
- Abbreviations and acronyms:
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
 - ICAO: International Civil Aviation Organisation
 - ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
 - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - DNEL: Derived No-Effect Level (REACH)
 - PNEC: Predicted No-Effect Concentration (REACH)
 - LC50: Lethal concentration, 50 percent

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.11.2018

Version number 4

Revision: 30.11.2018

Trade name: Akepox 1099 Komponente B

(Contd. of page 12)

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 2: Reproductive toxicity – Category 2
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
REACH directive 1907/2006/EC

· Sources

· * Data compared to the previous version altered.

Adaptation in accordance with REACH directive 1907/2006/EC

GB